



AudioCodes One Voice for Microsoft Lync Lync-Compatible IP Phones



AudioCodes 400HD Series Lync-Compatible IP Phones

The AudioCodes 400HD series of Lync-compatible IP phones offers enhanced voice quality and clarity for users of Microsoft Unified Communications. The phones' wide range of essential business features, reliability and certified interoperability make them the perfect choice for any Lync deployment, from small businesses up to large multi-site enterprises.

AudioCodes is a leading Microsoft partner with a complete offering of voice-enabling solutions for the Microsoft Lync Unified Communications (UC) market. In addition to IP phones, AudioCodes' portfolio for Lync includes media gateways, survivable branch appliances, enterprise session border controllers and call recording.



420HD is a cost-effective, feature-rich enterprise IP Phone. Its flexibility and robust design make it extremely suitable for a demanding enterprise and contact center deployments.

- Graphic multi-lingual LCD (128 X 48)
- 4 programmable soft keys
- Optional GbE Support



430HD is an advanced, mid-range enterprise IP Phone. Built for ease-of-use and convenience, the 430HD boasts a large LCD display and 12 programmable speed dial keys.

- Graphic multi-lingual LCD (132 X 64)
- 6 multi-function keys
- 12 programmable speed dial keys with presence monitoring
- 4 programmable soft keys
- Optional GbE Support



440HD is a high-end, executive IP phone. The 440HD includes a dedicated LCD screen displaying Lync contacts and their presence.

- Graphic multi-lingual LCD (132 X 64)
- 6 multi-function keys
- 12 programmable speed dial keys with presence monitoring
- Lync contacts with presence displayed on dedicated LCD (376 X 60)
- 4 programmable soft keys
- GbE Support

Benefit from full integration with Microsoft Unified Communications

BLF for co-workers presences (430/440HD models)

Enhanced "Better Together" support over Ethernet

Simple, secure sign-in

Lync contacts displayed on LCD screen (440HD model)

HD VoIP with full support for Microsoft's RTA codec*

USB Headset support (430/440HD models)

Provisioning and management (EMS) support

Boss Admin support (430/440HD models)

SBA mode support for branch survivability

* 1H 2015 roadmap feature

AudioCodes 400HD Series Lync-Compatible IP Phones

Powerful Set of Essential Enterprise Phone Features

- High-definition voice quality
- Multiple language support
- Mass management capabilities with AudioCodes EMS
- Better Together over Ethernet for easy sign in, click to call and Lync conferencing manageability
- Boss Admin support with 430HD and 440HD
- With Busy on Busy the 400HD Lync compatible phone will reject an incoming call while the user is engaged on another Lync call
- Direct access to the Lync contact list
- Voice quality monitoring
- Supplementary calling features (including Lync conferencing)
- Robust security mechanisms
- Power over Ethernet (PoE)
- Full duplex speakerphone and headset connectivity
- Available in black and white

Specifications for the 400HD Series

| Telephone Features | |
|--|--|
| Supplementary Features | Call Waiting, Call Hold, Call Transfer, Call Forward, support for Lync conferencing services, Hot Line, DND, Mute, Speed Dial, Dial Plan, CWRR, Call Logs, Auto Answer, Music on Hold, Busy on Busy, Call Pickup, Call Park, T9 Directory Search |
| Signaling | Caller ID, MWI, DTMF Relay - RFC2833, DTMF via SIP INFO, Configurable Call Progress Tones |
| Media Processing | |
| Wideband Voice Coders | G.722, Microsoft Real Time Audio (RTA ⁴) |
| Narrowband Voice Coders | G.711μ/a and RTA ⁴ |
| Additional Media Features | Acoustic echo cancellation (AEC) - multiple path, wideband acoustic EC, Packet Loss Concealment, Silence Suppression, Voice Activation Detection, Adaptive Jitter Buffer, Media Bypass |
| Protocol Support | |
| VoIP and Signaling | SIP – RFC 3261, SDP – RFC 2327, SIP over TCP/UDP/TLS, DNS_SRV (Redundancy), Digest authentication, PRACK, Early Media, SIP Subscribe notify, BLF (busy lamp field), Presence, MWI (message waiting indication), Call Admission Control, E911 |
| Data Protocols | IPv4, TCP, UDP, ICMP, ARP, RTP, SRTP, RTCP-XR, 802.1x, Static IP/DHCP IP Assignment, IEEE 802.1p/Q, QoS/ToS, HTTP/HTTPS/DHCP, NTP, FTP/TFTP, CDP/LLDP VLAN Configuration, LDAP, NAT and Firewall Traversal with STUN / TURN / ICE |
| Security | 802.1x, HTTPS, SIP over TLS and SRTP, Configuration file encryption, PC port disable option |
| Provisioning & Management | Web Server for Configuration and Management, Configuration update via FTP, TFTP, HTTP, HTTPS, DHCP Options (66,67,160,12,60,77), Mass Deployment Provisioning with TR-069 and TR-104 (client), Provision URL via SIP SUBSCRIBE and NOTIFY, Lync device in-band provisioning, EMS support |
| General Specifications | |
| Language support | English (default), Spanish, Italian, Portuguese, German, Russian, Ukrainian, Polish, French, Hebrew, Finnish |
| Telephone Interface | RJ-9 Headset Jack X 1, USB port for headset ¹ , DHSG ¹ |
| Network Interface | 2 LAN RJ-45 10/100/1000 Base-T for PC and LAN connectivity ² |
| Power Requirements | +12V DC, 1A Power adapter AC 100V-240V and/or Integrated Power over Ethernet - IEEE 802.3af (see price list for ordering options) |
| Storage/Operation Temperature | -20° to +70°C / 0° to +40°C (-4 to +158°F / 32 to +104°F) |
| Approvals, Safety and Country Certifications | FCC Part 15 Class B, ICES-003 Class B, EN55022 Class B, EN61000-3-2, EN61000-3-3, UL-60950-1, EN60950-1, IEC-60950-1 (CB), CE mark, cTUVus, Australia A-Tick, AS/NZS60950-1 and AS/ASIF S004, Brazil Anatel, Japan VCCI Class B |



Physical Specifications³

| | 420HD | 430HD | 440HD |
|---------------------------------|---|--|--|
| Unit Dimension (HxWxD) | 188 x 157 x 163 mm (7.40 x 6.18 x 6.41 in.) | 250 x 168 x 163 mm (9.84 x 6.61 x 6.42 in.) | 250 x 168 x 163 mm (9.84 x 6.61 x 6.42 in.) |
| Unit Weight | 0.82Kg (1.81 lb) | 1.00Kg (2.20 lb) | 1.05Kg (2.31 lb) |
| Unit Box Dimension (HxWxD) | 262 x 236 x 95 mm (7.40 x 6.18 x 6.41 in.) | 316 x 255 x 95 mm (9.84 x 6.61 x 6.42 in.) | 316 x 255 x 95 mm (9.84 x 6.61 x 6.42 in.) |
| Unit Box Weight | 1.2Kg (2.65 lb) | 1.44Kg (3.17 lb) | 1.49Kg (3.28 lb) |
| Master Carton Dimension (HxWxD) | 540 x 495 x 260 mm (7.40 x 6.18 x 6.41 in.) | 530 x 495 x 340 mm (20.87 x 19.49 x 13.39 in.) | 530 x 495 x 340 mm (20.87 x 19.49 x 13.39 in.) |
| Master Carton Weight | 13.1Kg (28.88 lb) | 15.73Kg (33.73 lb) | 15.8Kg (34.83 lb) |

¹ 430HD and 440HD models.

² GbE support is optional on the 420/430HD and supported by default on the 440HD.

³ The weights do not include an external Power Supply

⁴ 1H 2015 roadmap feature.



International Headquarters

1 Hayarden Street,
Airport City
Lod 7019900, Israel
Tel: +972-3-976-4000
Fax: +972-3-976-4040

AudioCodes Inc.

27 World's Fair Drive,
Somerset, NJ 08873
Tel: +1-732-469-0880
Fax: +1-732-469-2298

©2015 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, OSN, SmartTAP, VMAS, VolPerfect, VolPerfectHD, Your Gateway To VoIP and 3GX are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.

Ref # LTRM-20097 02/15 V.5

Contact us: www.audiocodes.com/info
Website: www.audiocodes.com

